

## ZPMV8.E116573 Wiring, Printed Certified for Canada - Component

Enhanced searching capability for this category can be found in UL's iQ Family of Databases ([iq.ul.com](http://iq.ul.com)).

[Page Bottom](#)

### Wiring, Printed Certified for Canada - Component

[See General Information for Wiring, Printed Certified for Canada - Component](#)

**GGP-SCHALTUNGEN GMBH**


E116573

AN DER LEEGE 2-4

37520 OSTERODE AM HARZ, GERMANY

Type	Cond Width		Cond	SS/ DSO	Max	Solder		Max	Flame	Meets	C
	Min	Edge			Area	Limits	Oper				
	mm(in)	mm(in)	Thk	Diam	C	sec	C	Class	UL796	T	
<b>Multilayer printed wiring boards.</b>											
<b>868</b>	0.08 (0.003)	0.08 (0.003)	16.5 (0.65) Int:105	DS	76.2 (3.0)	282	20	130	V-0	All	*
<b>874</b>	0.94 (0.037)	2.82 (0.111)	16.5 (0.65) Int:70	DS	12.8 (0.5)	270	10	130	V-0	All	4
<b>879</b>	0.08 (0.003)	0.08 (0.003)	16.5 (0.65) Int:102	DS	76.2 (3.0)	282	20	130	V-0	All	3
<b>881</b>	0.08 (0.003)	0.08 (0.003)	16.5 (0.65) Int:140	DS	76.2 (3.0)	282	20	130	V-0	All	3
<b>Multilayer printed wiring boards (mass laminated).</b>											
<b>870</b>	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	282	20	130	V-0	All	*
<b>878</b>	0.23 (0.009)	0.69 (0.027)	33 (1.30)	DS	25.4 (1.0)	260	20	105	V-0	All	-
<b>880</b>	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	260	20	130	V-0	All	*
<b>Single layer printed wiring boards.</b>											
<b>869</b>	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	282	20	130	V-0	All	*
<b>882</b>	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	282	20	120	V-0	▲	3

\* - Various CTI, may be marked on board

Marking: Company name or file number and type designation and Recognized Component Mark for Canada, . May be followed by a suffix to denote factory identification or burning test classification.

[Last Updated](#) on 2011-04-19

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".

## ZPMV2.E116573 Wiring, Printed - Component

Enhanced searching capability for this category can be found in UL's iQ Family of Databases ([iq.ul.com](http://iq.ul.com)).

[Page Bottom](#)

### Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

**GGP-SCHALTUNGEN GMBH**

E116573

AN DER LEEGE 2-4

37520 OSTERODE AM HARZ, GERMANY

Type	Cond Width		Cond	SS/ DS/	Max	Solder		Max	Flame	Meets	C
	Min	Edge			Area	Limits	Oper	UL796			
	mm(in)	mm(in)	Thk	DSO	Diam	C	sec	C	Class	DSR	I
<b>Multilayer printed wiring boards.</b>											
<b>868</b>	0.08 (0.003)	0.08 (0.003)	16.5 (0.65) Int:105	DS	76.2 (3.0)	282	20	130	V-0	All	*
<b>874</b>	0.94 (0.037)	2.82 (0.111)	16.5 (0.65) Int:70	DS	12.8 (0.5)	270	10	130	V-0	All	4
<b>879</b>	0.08 (0.003)	0.08 (0.003)	16.5 (0.65) Int:102	DS	76.2 (3.0)	282	20	130	V-0	All	3
<b>881</b>	0.08 (0.003)	0.08 (0.003)	16.5 (0.65) Int:140	DS	76.2 (3.0)	282	20	130	V-0	All	3
<b>Multilayer printed wiring boards (mass laminated).</b>											
<b>870</b>	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	282	20	130	V-0	All	*
<b>878</b>	0.23 (0.009)	0.69 (0.027)	33 (1.30)	DS	25.4 (1.0)	260	20	105	V-0	All	-
<b>880</b>	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	260	20	130	V-0	All	*
<b>Single layer printed wiring boards.</b>											
<b>869</b>	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	282	20	130	V-0	All	*
<b>882</b>	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	282	20	120	V-0	▲	3

\* - Various CTI, may be marked on board

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

[Last Updated](#) on 2011-04-19

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".